

扫二维码
关注谱尼测试

Pony Testing International Group

Report No.: MNIYU4YM87783716

MSDS Report

Sample Description
& Model

Lead-acid Battery FP1232

Applicant

ShenZhen FirstPower Technology Co., Ltd.

Address

RM, L, M, N 15/F BUILDING A, FORTUNE PLAZA
NO.7002, SHENNAN ROAD SHENZHEN CHINA



PONY 谱尼测试
Pony Testing International Group
Hotline 400-819-5688 www.ponytest.com



微信扫一扫，使用小程序 小程序扫一扫，在线验证
No.: MNIYU4YM87783716
Code: ta3e27



北京实验室: (010)82618116	长春实验室: (0431)85150908	石家庄实验室: (0311)85376660	武汉实验室: (027)83997127
上海实验室: (021)64851999	大连实验室: (0411)87336618	西安实验室: (029)89608785	合肥实验室: (0551)63843474
青岛实验室: (0532)88706866	哈尔滨实验室: (0451)88104651	呼和浩特实验室: (0471)3450025	广州实验室: (020)89224310
深圳实验室: (0755)26050909	郑州实验室: (0371)69350670	杭州实验室: (0571)87219096	厦门实验室: (0592)5568048
天津实验室: (022)27360730	新疆实验室: (0991)6684186	宁波实验室: (0574)87736499	成都实验室: (028)87702708
苏州实验室: (0512)62997900			



扫二维码
关注谱尼测试



Report No.: MNIYU4YM87783716 Date: 01.28.2019 Page 1 of 10

Pony Testing International Group

Material Safety Data Sheet

According to ST/SG/AC.10/30/Rev.7 (GHS)

Section 1 - Chemical Product and Company Identification

Chemical Product Identification

Sample Description: Lead-acid Battery

Sample Model: FP1232

Recommended Uses: Spare power, emergency power

Restrictions on Use: N/A

Supplier Name: HuiZhou FirstPower Technology Co., Ltd.

Address: Tai Yang Ao Industrial Zone Bai Hua Town, Hui Dong, Huizhou

Phone Number: 0752-8592666

FAX: 0752-8592621

E-mail: yh@efirstpower.com

Emergency Phone Number: 0752-8592666

Section 2 - Hazards Identification

Emergency overview: This product is a battery. Intended use of the product should not result in exposure to the chemical substance. In case of rupture the below hazards exist.

Classification according to GHS

Acute toxicity, oral (4)

Acute toxicity, inhalation: Dusts and mists (4)

Skin corrosion/irritation (1A, 1B, 1C)

Serious eye damage/eye irritation (1)

Carcinogenicity (1A, 1B)

Specific target organ toxicity, repeated exposure (2)

Hazardous to the aquatic environment, long-term hazard (1)

Label elements

Hazard pictogram(s):



Signal word:

Danger

Hazard statement(s):



扫微信二维码
关注谱尼测试



Report No.: MNIYU4YM87783716 Date: 01.28.2019 Page 2 of 10

Pony Testing International Group

H302 Harmful if swallowed

H332 Harmful if inhaled

H314 Causes severe skin burns and eye damage

H318 Causes serious eye damage

H360 May damage fertility or the unborn child

H373 May cause damage to organs through prolonged or repeated exposure

H410 Very toxic to aquatic life with long lasting effects

Precautionary statement(s):

Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dusts or mists.

P264 Wash skin and clothing thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves, protective clothing, eye protection, face protection.

Response:

P330 Rinse mouth.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER.

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P363 Wash contaminated clothing before reuse.

P321 Specific treatment(See additional emergency instructions).

P391 Collect spillage.

Storage

P405 Store locked up.

Disposal:

P501 Send contents to approved waste treatment plants.

Other hazards

Physical and chemical hazards: See Section 10

Human health hazards: See Section 11



Pony Testing International Group

Environmental hazards: See Section 12

Section 3 – Composition/Information on Ingredients

Chemical characterization: Mixture

Chemical Composition	CAS No.	EC#	Weight (%)
Lead	7439-92-1	231-100-4	70
Sulfuric acid	7664-93-9	231-639-5	10
Electrolyte	---	---	10

Section 4 - First Aid Measures

Description of first aid measures

General information No special measures required.

After eye contact

Flush eyes with plenty of water for several minutes while holding eyelids open. Get medical attention if irritation persists.

After skin contact

Remove contaminated clothing and shoes. Immediately wash with water and soap and rinse thoroughly. Wash clothing and shoes before reuse. If irritation occurs, get medical attention.

After inhalation

Remove victim to fresh area. Administer artificial respiration if breathing is difficult. Seek medical attention.

After swallowing

Do not induce vomiting. Get medical attention.

Personal protective equipment for first-aid responders: No data available.

Most important symptoms/effects, acute and delayed: No data available.

Indication of immediate medical attention and special treatment needed: Treat symptomatically.

Section 5 - Fire Fighting Measures

Suitable extinguishing media:

Small Fire: Dry chemical, CO₂ or water spray. Large Fire: Dry chemical, CO₂, alcohol-resistant foam or water spray. Move containers from fire area if you can do it without



扫微信二维码
关注谱尼测试



Report No.: MNIYU4YM87783716 Date: 01.28.2019 Page 4 of 10

Pony Testing International Group

risk. Dike fire-control water for later disposal; do not scatter the material.

Unsuitable extinguishing media:

No data available.

Specific Hazards arising from the chemical:

Special hazards arising from the substance or mixture

Battery may burst and release hazardous decomposition products when exposed to a fire situation. TOXIC; inhalation, ingestion or skin contact with material may cause severe injury or death. Contact with molten substance may cause severe burns to skin and eyes. Avoid any skin contact. Effects of contact or inhalation may be delayed. Fire may produce irritating, corrosive and/or toxic gases. Runoff from fire control or dilution water may be corrosive and/or toxic and cause pollution.

Specific protective actions for fire-fighters:

Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing will only provide limited protection.

Section 6 - Accidental Release Measures

Personal precautions:

As an immediate precautionary measure, isolate spill or leak area in all directions for at least 50 meters (150 feet) for liquids and at least 25 meters (75 feet) for solids. Keep unauthorized personnel away. Stay upwind, uphill and/or upstream. Ventilate the area before entry.

Protective equipment:

No data available.

Emergency procedures:

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Stop leak if you can do it without risk. Prevent entry into waterways, sewers, basements or confined areas. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. DO NOT GET WATER INSIDE CONTAINERS.

Environmental precautions:

Do not allow material to be released to the environment without proper governmental permits.

Methods and materials for containment and cleaning up:

For all waste handling must refer to United Nations, National and Local Regulations for disposal.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.



Pony Testing International Group

See Section 13 for disposal information.

Section 7 - Handling and Storage

Precautions for safe handling:

Do not short or install with incorrect polarity. Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps.

Conditions for safe storage, including any incompatibilities:

Store in a cool, dry, well-ventilated place. Keep away from heat, avoiding the long time of sunlight. Keep container tightly sealed.

Section 8 - Exposure Controls/Personal Protection

Control parameters

CAS No.	ACGIH	NIOSH	OSHA
7439-92-1	TLV-TWA 0.05mg/m ³	N/A	PEL-TWA 0.2mg/m ³
7664-93-9	TLV-TWA 0.2mg/m ³	REL-TWA 1mg/m ³	PEL-TWA 1mg/m ³

Appropriate engineering controls:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Remove all soiled and contaminated clothing immediately.

Wash hands before breaks and at the end of work.

Personal Protective Equipment:

Respiratory protection: Wear suitable protective mask. For a large large number of battery leakages, wear chemical protective clothing, including self-contained breathing apparatus.

Hand Protection: Wear appropriate protective gloves to reduce skin contact.

Eye Protection: Wear safety goggles or eye protection combined with respiratory protection.

Skin and Body Protection: Working environment required, wear suitable protective clothing to minimize contact with skin. The type of protective equipment must be according to the concentration and the content of certain hazardous substances in the workplace.

Section 9 - Physical and Chemical Properties



扫二维码
关注谱尼测试



Report No.: MNIYU4YM87783716 Date: 01.28.2019 Page 6 of 10

Pony Testing International Group

Information on basic physical and chemical properties

General information

Appearance:	Black.
Form:	Prismatic.
Odour:	Not available.
Odour threshold:	Not available.
pH:	Not available.
Melting point/freezing point:	Not available.
Initial boiling point and boiling range:	Not available.
Flash Point:	Not available.
Evaporation rate:	Not available.
Flammability (solid, gas):	Not available.
Explosion Limits (vol% in air):	Not available.
Vapour pressure, kPa at 20°C:	Not available.
Vapor density:	Not available.
Density/Relative density (water = 1):	Not available.
Solubility(ies):	Not available.
Partition coefficient: n-octanol/water:	Not available.
Auto-ignition temperature:	Not available.
Decomposition temperature:	Not available.
Viscosity:	Not available.
Other information:	
Voltage	12V
Electric capacity	3.2Ah

Section 10 - Stability and Reactivity

Reactivity: No data available.

Chemical stability: Stable.

Possibility of hazardous reactions: No data available.

Conditions to Avoid: Flames, sparks, and other sources of ignition, incompatible materials.

Incompatible materials: Oxidizing agents, acid base.

Hazardous decomposition products: Carbon monoxide, carbon dioxide.



Section 11 - Toxicological Information

Acute Toxicity:

CAS No.	LC50/LD50
7439-92-1	No data available.
7664-93-9	LD50 Rat (oral): 2140mg/kg

Skin irritation/corrosion:

Eye damage/irritation: No data available.

Respiratory or Skin sensitisation: No data available.

Reproductive Cell Mutagenicity: No data available.

Carcinogenicity: No data available.

Reproductive Toxicity: No data available.

Specific target organ toxicity-Single exposure: No data available.

Specific target organ toxicity-Repeated exposure: No data available.

Aspiration hazard: No data available.

Potential Health Effects: No data available.

Inhalation: No data available.

Skin contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Section 12 - Ecological Information

Ecological Toxicity:

CAS# 7664-93-9

LC50: 16-28mg/L- fishes (Bluegill) - 96h

Persistence and degradability: No data available.

Bioaccumulative Potential: No data available.

Mobility in Soil: No data available.

Other adverse effects: No data available.

Section 13 - Disposal Considerations

Disposal methods:

Recommendation:



扫微信二维码
关注谱尼测试



Report No.: MNIYU4YM87783716 Date: 01.28.2019 Page 8 of 10

Pony Testing International Group

Consult state, local or national regulations to ensure proper disposal.

Uncleaned packaging

Recommendation: Disposal must be made according to official regulations.

Section 14 - Transport Information

UN Number	
IATA	UN2800
IMDG	UN2800
Model Regulation	UN2800
UN Proper shipping name	
IATA	Batteries, wet, non-spillable
IMDG	BATTERIES, WET, NON-SPILLABLE
Model Regulation	BATTERIES, WET, NON-SPILLABLE
Transport hazard class(es)	
IATA	8
IMDG	8
Model Regulation	8
Packing group	
IATA	N/A
IMDG	N/A
Model Regulation	N/A
Packaging Sign	
IATA	N/A
IMDG	N/A
Model Regulation	N/A
Environmental hazards	
Marine pollutant:	No
Special precautions for user	No information available.

Transport information: Lead-acid Battery FP1232 has passed the Vibration test, Pressure differential test, Non-spillable test, according to the report ID: MDIJHYBN40099721.

According to the Special Provisions A67 of IATA DGR 60th Edition. The goods are not subject to other provision of this code.

According to the special provision 238 of IMDG (38-16) or the special provision 238 of



扫微信二维码
关注谱尼测试



Report No.: MNIYU4YM87783716 Date: 01.28.2019 Page 9 of 10

Pony Testing International Group

<<Recommendations On The Transport Of Dangerous Goods-Model Regulations>> (20th).

The goods are not subject to other provision of this code.

Separate batteries when shipping to prevent short-circuiting. They should be packed in strong packaging for support during transport.

Transport Fashion: By air, by sea, by railway, by road.

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

CAS No.	TSCA	IECSC	DSL/NDSL	EINECS/ ELINCS/ NLP
7439-92-1	Listed	Listed	Listed DSL	Listed
7664-93-9	Listed	Listed	Listed DSL	Listed

Section 16 - Other Information

Issue Time: 2019-01-28

Issue Department: Technical department

Modification record:

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Other Information:

CAS: (Chemical Abstracts Service);

EC: (European Commission);

ACGIH: (American Conference of Governmental Industrial Hygienists);

NIOSH: (US National Institute for Occupational Safety and Health);

OSHA: (US Occupational Safety and Health);

TLV: (Threshold Limit Value)

TWA: (Time Weighted Average);



扫二维码
关注谱尼测试



Report No.: MNIYU4YM87783716 Date: 01.28.2019 Page 10 of 10

Pony Testing International Group

STEL: (Short Term Exposure Limit);
 PEL: (Permissible Exposure Level);
 REL: (Recommended Exposure Limit);
 PC-STEL: (Permissible concentration-time weighted average);
 PC-TWA: (Permissible concentration-short time exposure limit);
 LC50: (Lethal concentration, 50 percent kill);
 LD50: (Lethal dose, 50 percent kill);
 IARC: (International Agency for Research on Cancer);
 EC50: (Median effective concentration);
 BCF: (Bioconcentration Factor);
 BOD: (Biochemical oxygen demand);
 NOEC: (No observed effect concentration);
 NTP: (US National Toxicology Program);
 RTECS: (Registry of Toxic Effects of Chemical Substances);
 IATA: (International Air Transport Association);
 IMDG: (International Maritime Dangerous Goods);
 TDG: (Recommendations on the TRANSPORT OF DANGEROUS GOODS Model Regulations);
 TOC: (Total Organic Carbon);
 TSCA: (Toxic Substances Control Act of USA);
 DSL: (the Domestic Substances List of Canada);
 NDSL: (the Non-domestic Substances List of Canada)

End of report